

a) Hersteller manufacturer's name		AEREX HaustechnikSysteme GmbH				
b) Modellkennung (Code) manufacturer's model identifier (code)		Reco-Boxx 2100 Flat-H-R / EV / EN (0040.2068)				
c) Typ typology		RVU	–	BVU	x	
		NRVU	x	UVU	–	
d) Art des eingebauten / einzubauenden Antriebes type of drive installed / intended to be installed		multi-speed	–	installed	–	
		VSD	x	intended to be instal.	–	
e) Art des WRS type of HRS		Kreislaufver. / run-around	–	anderes / other	x	keines / none
						–
f) Thermischer Übertragungsgrad der WRG thermal efficiency of heat recovery	η_{t_nrvu}	80			%	
g) Nenn-Luftvolumenstrom der NWLA nominal NRVU flow rate	q_{nom}	0,28			m³/s	
h) Tatsächliche elektrische Eingangsleistung effective electric power input	p	0,51			kW	
i) Innere spezifische Ventilatorleistung internal specific fan power	SFP_{int}	523			W/(m³/s)	
j) Anströmgeschwindigkeit face velocity		1,77			m/s	
k) Nennaußendruck nominal external pressure	$\Delta p_{s,ext}$	100			Pa	
l) Interner Druckabfall von Lüftungsbauteilen internal pressure drop ventilation components	$\Delta p_{s,int}$	168			Pa	
m) Interner Druckabfall von Nichtlüftungsbauteilen internal pressure drop non-ventilation components	$\Delta p_{s,add}$	168			Pa	
n) Statischer Wirkungsgrad Ventilator static efficiency of fans (RegulationNr. 327/2011)	η_{fan}	40			%	
o) Äußere Höchstlecklufttrate declared maximum external leakage rate		L3 (<3%)			%	
Innere Höchstlecklufttrate declared maximum internal leakage rate		2			%	
p) Energetische Eigenschaften der Filter energy performance of the filters		–			kWh/a	
q) Beschreibung optische Filterwarnanzeige description of visual filter warning		LED - replace the filter continuously to preserve the device properties				
r) Gehäuse-Schalleistungspegel casing sound power level	L_{WA}	66			dB[A]	
s) Internetadresse für Anweisungen zur Zerlegung/Demontage internet address for disassembly instructions		www.aerex.de				